

## The Ultimate in Wide-Format Finishing with Complete Control

To satisfy the demand for finishing increasingly wide inkjet and photographic prints, SEAL® Brands has a new laminator; the SEAL® Image® 80S.

The SEAL® Image® 80S is a top-heated roller laminator, capable of mounting and laminating prints up to 80" (2,030 mm) in width, and is ideal for high-volume production.

It allows the user full control over temperature, speed and pressure for adjustment of machine settings to match individual processing requirements. The 'drop-in' auto-grip shafts allow for easy, fast loading of materials and the laminator also has the function of 'edge wrapping' for finishing high-quality mounted displays.

For the ultimate in wide-format finishing, combine the SEAL® Image® 80S with the SEAL® Brands range of 79" (2 metre) materials; SEAL® Print Mount® mounting adhesive, SEAL® Print Shield® gloss and matte overlaminates.

### Features

- Touch-pad control panel which allows for independent control of speed, temperature, laminating pressure and substrate thickness
- High-release silicone rollers for consistent production and easy cleaning
- 7-segment L.E.D. setting indicators
- Swing-out arm control panel enabling operation from front or rear of machine
- 'Drop-in' auto-grip shafts for easy loading and positioning of materials
- Simple, integral film tension adjustment on auto-grip shafts
- Automated 'edge wrapping' function ensuring neat edges on rigid displays
- Automatic upper take-up shaft for removing release liners
- Swinging in-feed table for easy material loading
- Roll-to-roll feature allows for processing of rolls of media
- Manually adjustable temperature settings from 0-250°F (0-120°C)
- Microprocessor controller for even temperature control
- Foot switch for hands-free operation
- Comprehensive safety system with emergency stops and self-testing optical safety guard
- CE and cETL certified
- Sturdy, stand-alone design with casters and levelling feet
- Quiet mechanical operation



*Touch-pad control which allows for independent control of speed, temperature, laminating pressure and substrate thickness.*



*'Drop-in' auto-grip shafts for easy loading and positioning of materials.*



*'Edge-wrapping' function ensuring neat edges on rigid displays*



# SEAL® Image® 80S Laminator

## SPECIFICATIONS

Specifications	Image® 80S
Maximum working width	80" (2,030 mm)
Maximum heated width	80" (2,030 mm)
Maximum speed	16.3 ft./min. (5 m/min)
Maximum roller speed	11/8" (30 mm)
Dimensions	Width: 107" (2,700 mm) Depth: 23" (580 mm) (excluding tables) Depth: 32" (810 mm) (including tables) Height: 51" (1,300 mm) (excluding control panel) 65.5" (1,660 mm) (including control panel)
Net weight	1,327 lbs (602 kg)
Transport Dimensions	Height: 59" (1,500 mm), Width: 37" (950 mm) Length: 112" (2,850 mm), Weight: 1,477 lbs. (670 kg)
Electrical requirements	1N/PE-200-250 V, 50/60Hz 25A 3N/PE-200-250 V, 50/60Hz 25 A
Maximum power consumption	6,250 Watts

Note: It is recommended that your main power be installed by a licensed electrician in accordance with electrical codes in your area. Specifications subject to change without notice.

SEAL® Brands, Image®, Print Mount® and Print Shield® are registered trademarks of Hunt Corporation.

**Seal Graphics Americas Corporation**  
7091 Troy Hill Drive  
Elkridge, MD 21075  
Tel: 410-379-5400  
Fax: 410-579-8960

**Seal Graphics Canada**  
1601 Matheson Blvd. E.  
Mississauga, Ontario  
Canada, L4W 1H9  
Tel: 905-212-9232  
Fax: 905-212-9313

**Seal Graphics U.K. Ltd**  
Unit 1, 1 Watkins Close  
Burnt Mills Industrial Estate  
Basildon, Essex SS13 1BJ  
United Kingdom  
Tel: +44 1268 530 331  
Fax: +44 1268 729 442

**Seal Graphics Europe BV**  
Kanaaldijk O.Z.3  
P.O.Box 29,  
8100 AA Raalte  
The Netherlands  
Tel: +31 572 345 500  
Fax: +31 572 345 501

**Seal Graphics Pacific Limited**  
Unit A, 13th Floor, Block 1  
Leader Industrial Centre  
Tsuen Wan,  
New Territories, Hong Kong  
Tel: +852 2407 3738  
Fax: +852 2408 0973



Contact your local distributor:

